

SPECIFICATION

Power Handling 6 watts
Rated Input 100 volt
Transformer Tappings 6, 3, 1.5, 0.75 watts
SPL (1w/1m) 93dB
Max SPL (rated/1m) 100dB
Frequency Response 100Hz – 20kHz
Dimensions (diameter x depth) 230mm x 127mm
Cutout Size (diameter) 200mm
Material High impact ABS
Weight (inc. packaging) 1.0 kg
Dispersion 1kHz/4kHz 120⁰ / 90⁰
Colour White

OTHER PRODUCTS AND SYSTEMS AVAILABLE ...

- FIRE TELEPHONE SYSTEM WITH A CHOICE OF HANDSET STYLES
- CAMERA OPERATED VOICE MESSAGE SYSTEMS
- STANDARD & CUSTOM MANUFACTURED LOUDSPEAKERS
- PRISON CELL INTERCOM & PAGING SYSTEMS
- EXPLOSION PROOF INTERCOM & PAGING AMPLIFIERS
- CUSTOM MANUFACTURED INTERCOM, LONGWIRE TELEPHONE & TALKBACK SYSTEMS
- TELEPHONE & INTERCOM ANCILLARIES INCLUDING ACOUSTIC BOOTHS, FLASHING BEACONS & SOUNDERS
- DISABLED REFUGE INTERCOM
- CUSTOM MICROPHONE CONSOLES
- VOLUME CONTROLS
- VOICE ALARM SYSTEMS

INTAK

UNIT 41, CRIFTIN PARK, OXTON, NOTTINGHAMSHIRE. NG14 6AT
TELEPHONE: (0115) 965 6598 — FAX: (0115) 965 6546