

SPECIFICATION

Power Handling 6 watts

Rated Input 100 volt

Transformer Tappings 6, 3, 1.5, 0.75 watts

SPL (1w/1m) 93dB

Max SPL (rated/1m) 101B

Frequency Response 130Hz – 18kHz

Dimensions (height x width x depth) 140 x 140 x 85

Material steel

Dispersion 1KHz/4KHz 178°/82°

Weight (inc. packaging) 2.5kg

Colour White RAL 9010

OTHER PRODUCTS AND SYSTEMS AVAILABLE ...

- FIRE TELEPHONE SYSTEM WITH A CHOICE OF HANDSET STYLES
- CAMERA OPERATED VOICE MESSAGE SYSTEMS
- STANDARD & CUSTOM MANUFACTURED LOUDSPEAKERS
- PRISON CELL INTERCOM & PAGING SYSTEMS
- EXPLOSION PROOF INTERCOM & PAGING AMPLIFIERS
- CUSTOM MANUFACTURED INTERCOM, LONGWIRE TELEPHONE & TALKBACK SYSTEMS
- TELEPHONE & INTERCOM ANCILLARIES INCLUDING ACOUSTIC BOOTHS, FLASHING BEACONS & SOUNDERS
- DISABLED REFUGE INTERCOM
- CUSTOM MICROPHONE CONSOLES
- VOLUME CONTROLS
- VOICE ALARM SYSTEMS

INTAK

UNIT 41, CRIFTIN PARK, OXTON, NOTTINGHAMSHIRE. NG14 6AT
TELEPHONE: (0115) 965 6598 — FAX: (0115) 965 6546