

SPECIFICATION

Power Handling 6 watts

Rated Input 100 volt

Transformer Tappings 6, 3, 1.5, 0.75 watts

SPL (1w/1m) 95dB

Max SPL (rated/1m) 102dB

Frequency Response 92Hz – 20kHz

Dimensions (diameter x depth) 180mm x 131mm

Cutout Size (diameter) 160mm

Material steel

Weight (inc. packaging) 2.1kg

Dispersion 1kHz/4kHz 133⁰ / 52⁰

Colour White RAL 9003

OTHER PRODUCTS AND SYSTEMS AVAILABLE ...

- FIRE TELEPHONE SYSTEM WITH A CHOICE OF HANDSET STYLES
- CAMERA OPERATED VOICE MESSAGE SYSTEMS
- STANDARD & CUSTOM MANUFACTURED LOUDSPEAKERS
- PRISON CELL INTERCOM & PAGING SYSTEMS
- EXPLOSION PROOF INTERCOM & PAGING AMPLIFIERS
- CUSTOM MANUFACTURED INTERCOM, LONGWIRE TELEPHONE & TALKBACK SYSTEMS
- TELEPHONE & INTERCOM ANCILLARIES INCLUDING ACOUSTIC BOOTHS, FLASHING BEACONS & SOUNDERS
- DISABLED REFUGE INTERCOM
- CUSTOM MICROPHONE CONSOLES
- VOLUME CONTROLS
- VOICE ALARM SYSTEMS

INTAK

UNIT 41, CRIFTIN PARK, OXTON, NOTTINGHAMSHIRE. NG14 6AT
TELEPHONE: (0115) 965 6598 — FAX: (0115) 965 6546