

SPECIFICATION

Power Handling 25 watts
Rated Input 100 volt
Transformer Tappings 250, 15, 7.5, 3.75 watts
SPL (1w/1m) 112dB
Max SPL (rated/1m) 128dB
Frequency Response 260Hz – 14.2KHz
IP rating IEC 529 IP66
Dispersion 1KHz/4KHz 119°/52°
Dimensions (diameter x depth) 210mm x 286mm
Material High impact ABS
Weight 4.2kg
Colour Light grey, RAL 7036

OTHER PRODUCTS AND SYSTEMS AVAILABLE ...

- FIRE TELEPHONE SYSTEM WITH A CHOICE OF HANDSET STYLES
- CAMERA OPERATED VOICE MESSAGE SYSTEMS
- STANDARD & CUSTOM MANUFACTURED LOUDSPEAKERS
- PRISON CELL INTERCOM & PAGING SYSTEMS
- EXPLOSION PROOF INTERCOM & PAGING AMPLIFIERS
- CUSTOM MANUFACTURED INTERCOM, LONGWIRE TELEPHONE & TALKBACK SYSTEMS
- TELEPHONE & INTERCOM ANCILLARIES INCLUDING ACOUSTIC BOOTHS, FLASHING BEACONS & SOUNDERS
- DISABLED REFUGE INTERCOM
- CUSTOM MICROPHONE CONSOLES
- VOLUME CONTROLS
- VOICE ALARM SYSTEMS

INTAK

UNIT 41, CRIFTIN PARK, OXTON, NOTTINGHAMSHIRE. NG14 6AT
TELEPHONE: (0115) 965 6598 – FAX: (0115) 965 6546